


MAPEC

M O V I N G S O L U T I O N S



Rotelle

Wheels



ASSI CON ROTELLE SERIE GRA

Sono previsti con rotelle RSR 48 e RSR 131 distanziate fra di loro con tubetto in PVC.


Possono essere preferiti ai rulli nei trasportatori a gravità, con particolare funzionalità nelle curve, per la movimentazione di colli a superficie d'appoggio piana.

Si consiglia l'esecuzione standard per poter montare gli assi con le rotelle sfalsate fra di loro, e la struttura portante con sostegno centrale.

WHEELED SHAFTS SERIES GRA

They are supplied with RSR 48 and RSR 131 wheels with PVC tube spacing and they can be preferred to the rollers in gravity conveyors with particular curve functionality and to handle packages having flat contact surfaces.

We suggest using the standard execution for an assembly of shafts with offset wheels and central stand supporting structure.



Con rotelle RSR 48 / With wheels RSR 48

Codice di ordinazione Ordering Codes		Rotelle Wheels	Peso Weight
Tipo Type	Lunghezza Length C	N.	daN
GRA/8	284	3	0,335
GRA/9	384	4	0,450
GRA/10	484	5	0,575
GRA/11	584	6	0,690
GRA/12	684	7	0,800
GRA/13	784	8	0,910
GRA/14	884	9	1,030

Con rotelle RSR 131 / With wheels RSR 131

Codice di ordinazione Ordering Codes		Rotelle Wheels	Peso Weight
Tipo Type	Lunghezza Length C	N.	daN
GRA/58	284	3	0,200
GRA/59	384	4	0,265
GRA/60	484	5	0,345
GRA/61	584	6	0,415
GRA/62	684	7	0,480
GRA/63	784	8	0,545
GRA/64	884	9	0,615

VIA MONTE BIANCO 15/17
20833 GIUSSANO - MB

.....
INFO@MAPEC.NET
WWW.MAPEC.NET
T 0362 311684
F 0362311007